# HP Designjet T120 ePrinter

# 

#### An easy-to-use, web-connected 24-inch printer



#### More for your money

- Two printers in one. Print from A4/Letter to A1/D using the A3/B+ tray and 24-inch (610 mm) wide front-loading media roll.
- Install your printer where it's most convenient and work where you want, thanks to Wi-Fi connectivity<sup>1</sup>.
- Take control of your print jobs by plotting them in-house, saving time and money.
- Enable outstanding print quality and high productivity with Original HP inks and long-life printheads.

#### **Compact and easy to use**

- Easily fit this printer—the smallest in its class—where you need it in your studio.
- The intuitive, full-color, 4.3-inch (109 mm) touchscreen simplifies navigation and printing.
- Complete your work quickly and accurately, thanks to true print previews from the driver.

#### Print from virtually anywhere<sup>2</sup>

- Use your Apple<sup>®</sup> or Android<sup>™</sup> smartphone or tablet to print from virtually anywhere<sup>2</sup>.
- Access and print projects when you're away from your studio, using HP Designjet ePrint & Share<sup>2</sup>.
- Automatically save copies of your work to the cloud when you print using HP Designjet ePrint & Share<sup>2</sup>.
- Email projects to your HP Designjet T120 ePrinter and print, thanks to its web connectivity features<sup>2</sup>.

### For more information, please visit <a href="https://www.hp.com/go/DesignjetT120">hp.com/go/DesignjetT120</a>

HP Designjet ePrint & Share allows you to print to your HP Designjet ePrinter from your Apple® or Android<sup>™</sup> smartphone or tablet—helping you get work done even when you're away from the studio<sup>2</sup>. hp.com/go/eprintandshare

- <sup>1</sup> Wireless performance is dependent on physical environment and distance from access point, and may be limited during active VPN connections. Supports IEEE 802.11 b/g.
- <sup>2</sup> Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple<sup>®</sup> iOS or Android<sup>™</sup> device and Internet connection are required. Data or connection charges may apply. Print times may vary. For more information visit hp.com/go/eprintandshare.

#### **Technical specifications**

Color images <sup>4</sup> Fast: 22.4 m²/hr (241 ft²/hr) on coated media Best: 2.3 m²/hr (25 ft²/hr) on glossy mediaPrint resolutionUp to 1200 x 1200 optimized dpiMargins (top x bottom x left x right)Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 x 0.2 in Sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 x 0.2 in sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 x 0.2 in sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 x 0.2 in right)TechnologyHP Thermal Inkjet Ink typesInk typesDye-based (C, M, Y); pigment-based (K) Ink dropInk drop5.5 pl (C, M, Y); 12 pl (K)Printheads1 (C, M, Y, K)Line accuracy+/- 0.1%5Minimum line width0.04 mm (0.0016 in) (HP-GL/2 addressable) widthGuaranteed mini- ouranteed mini-0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))^6 mum line widthMediaHandlingSheet feed, roll feed, input tray, automatic cutter WeightMediaHandlingSheet feed, roll freed, input tray, automatic cutter WeightSizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)ThicknessUp to 11.8 milMemory256 MBConnectivityInterfaces (standard)Print IngugagesHP PCL 3 GUI, JPEG (standard)Printer987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in) (w x d x h)Shipping1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)WeightPrinter987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in) (w x d x h)WeightPrinterPr				
Print resolution   Up to 1200 x 1200 optimized dpi     Margins (top x bottom x left x right)   Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.1	Line drawings <sup>3</sup> 70 sec/page on A1/D, 40 A1/D prints per hour   Color images <sup>4</sup> Fast: 22.4 m <sup>2</sup> /hr (241 ft <sup>2</sup> /hr) on coated media			
Margins (top x bottom x left x right)Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.				
botiom x left x right)Sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in right)TechnologyHP Thermal InkjetInk typesDye-based (C, M, Y); pigment-based (K)Ink drop5.5 pl (C, M, Y); 12 pl (K)Printheads1 (C, M, Y, K)Line accuracy+/- 0.1%5Minimum line0.04 mm (0.0016 in) (HP-GL/2 addressable)widthGuaranteed mini- mum line widthGuaranteed mini- mum line width0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))6MediaHandlingSheet feed, roll feed, input tray, automatic cutter (input tray)SizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)ThicknessUp to 11.8 milMemory256 MBConnectivityInterfaces (standard)Print languages (standard)Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint Drivers (included)Dimensions (w x d x h)PrinterMeightPrinterPrinter987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in) ShippingMat's in the boxPrinterHP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cordEnvironmental poperating humidity: 20 to 80% RHAcousticSound power: 6.5 B(A) (active); < 1.6 dB(A) (standby)				
Ink types   Dye-based (C, M, Y); pigment-based (K)     Ink drop   5.5 pl (C, M, Y); 12 pl (K)     Printheads   1 (C, M, Y, K)     Line accuracy   +/- 0.1%5     Minimum line   0.04 mm (0.0016 in) (HP-GL/2 addressable)     width   Guaranteed mini-     Guaranteed mini-   0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))6     Media   Handling   Sheet feed, roll feed, input tray, automatic cutter     Weight   60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)     Size   Rolls: 279 to 610 mm (11 to 24 in)     Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x74.7 in)   Standard sheets: A4, A3, A2, A1 (A, B, C, D)     Thickness   Up to 11.8 mil     Memory   256 MB     Connectivity   Interfaces     Interfaces   Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)     Print languages   HP PCL 3 GUI, JPEG     (standard)   Printer and the printing, Apple AirPrint     Drivers (included)   HP PCL 3 GUI driver for Mac OS X and Windows®     Dimensions   Printer   987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)     (w x d x h)   Shipping   1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)     Weight	)			
Ink drop   5.5 pl (C, M, Y); 12 pl (k)     Printheads   1 (C, M, Y, K)     Line accuracy   +/- 0.1%5     Minimum line   0.04 mm (0.0016 in) (HP-GL/2 addressable)     width   Guaranteed mini- mum line width   0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))6     Media   Handling   Sheet feed, roll feed, input tray, automatic cutter     Weight   60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)     Size   Rolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in)     Size   Rolls: 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in)     Standard sheets: A4, A3, A2, A1 (A, B, C, D)   Thickness     Memory   256 MB     Connectivity   Interfaces (standard)   Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)     Print languages   HP PCL 3 GUI, JPEG (standard)   Printerfaces     Print languages   Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint     Drivers (included)   HP PCL 3 GUI driver for Mac OS X and Windows®     Dimensions   Printer   987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)     (w x d x h)   Shipping   30 kg (66.1 lb)     What's in the box   HP Designjet T120 ePrinter, printhead, introductory ink				
Printheads   1 (C, M, Y, K)     Line accuracy   +/- 0.1%5     Minimum line width   0.04 mm (0.0016 in) (HP-GL/2 addressable) width     Guaranteed mini- mum line width   0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))6     Media   Handling   Sheet feed, roll feed, input tray, automatic cutter Weight     60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)   Size     Size   Rolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in)     Standard sheets: A4, A3, A2, A1 (A, B, C, D)   Thickness     Up to 11.8 mil   Memory     Z56 MB   Interfaces     Connectivity   Interfaces     Interfaces   Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)     Wi-Fi   Print languages     Print languages   HP PCL 3 GUI driver for Mac OS X and Windows®     Dimensions   Printer   987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)     (w x d x h)   Shipping   1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)     Weight   Printer   25.5 kg (56.2 lb)     Shipping   30 kg (66.1 lb)   Shipping     What's in the box   HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power				
Line accuracy+/- 0.1%5Minimum line width0.04 mm (0.0016 in) (HP-GL/2 addressable) widthGuaranteed mini- mum line width0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))6MediaHandlingSheet feed, roll feed, input tray, automatic cutted Weight60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)SizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)Memory256 MBConnectivityInterfaces (standard)Interfaces (standard)Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)Print languages (standard)PP PCL 3 GUI, JPEG (standard)Dimensions (w x d x h)Printer ShippingPrinter Drivers (included)HP PCL 3 GUI driver for Mac OS X and Windows®Dimensions (w x d x h)Printer ShippingMat's in the boxHP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cordEnvironmental Congerating temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RHAcoustic Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)				
Minimum line width0.04 mm (0.0016 in) (HP-GL/2 addressable)Guaranteed mini- mum line width0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))6MediaHandlingSheet feed, roll feed, input tray, automatic cutted WeightGo to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)SizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)Memory256 MBConnectivityInterfaces (standard)Interfaces (standard)Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)WeightOrigonal Print languages (standard)Print languages (standard)PP PCL 3 GUI, JPEGDimensions (w x d x h)Printer ShippingPrinter Shipping987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in) ShippingMat's in the boxPrinter PrinterPrinter Storage temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RHAcoustic Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)				
widthGuaranteed minimum line widthMediaHandlingSheet feed, roll feed, input tray, automatic cutterWeight60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)SizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)ThicknessUp to 11.8 milMemory256 MBConnectivityInterfaces(standard)Wrint languages(standard)Print languages(standard)Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrintDrivers (included)HP PCL 3 GUI driver for Mac OS X and Windows®Dimensions (w x d x h)Shipping1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)WeightPrinter25.5 kg (56.2 lb) ShippingShipping30 kg (66.1 lb)What's in the boxHP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cordEnvironmental conge temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RHAcousticSound power: 6.5 B(A) (active); < 3.4 B(A) (standby)				
mum line widthMediaHandlingSheet feed, roll feed, input tray, automatic cuttedWeight60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)SizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)Memory256 MBConnectivityInterfaces (standard)Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)Print languages (standard)Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrintDimensions (w x d x h)Printer 987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in) Shipping1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)Weight boxPrinter25.5 kg (56.2 lb) Shipping30 kg (66.1 lb)What's in the boxHP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cordEnvironmental rangesOperating temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RHAcoustic Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)Power< 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)				
Weight60 to 280 g/m² (roll/manual feed); 60 to 220 g/ (input tray)SizeRolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)Memory256 MBConnectivityInterfaces (standard)Print languages (standard)Print languages (standard)Printer gathsPrinter driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrintDimensions (w x d x h)Printer987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in) ShippingMet d x hShipping1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)WeightPrinter25.5 kg (56.2 lb) ShippingShipping30 kg (66.1 lb)What's in the boxHP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cordEnvironmental rangesQperating temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RHAcoustic Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)				
(input tray)       Size     Rolls: 279 to 610 mm (11 to 24 in) Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)       Thickness     Up to 11.8 mil       Memory     256 MB       Connectivity     Interfaces (standard)       Print languages (standard)     Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)       Print languages (standard)     Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint       Drivers (included)     HP PCL 3 GUI driver for Mac OS X and Windows®       Dimensions (w x d x h)     Printer       Printer     987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)       Shipping     1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)       Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental ranges     Operating temperature: -25 to 55°C (-13 to 131°F)       Operating humidity: 20 to 80% RH     Acoustic       Acoustic     Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)	r			
Sheets: 210 x 279 to 610 x 1897 mm (8.3 x 11 to 24 x 74.7 in) Standard sheets: A4, A3, A2, A1 (A, B, C, D)       Thickness     Up to 11.8 mil       Memory     256 MB       Connectivity     Interfaces     Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)       Wi-Fi     Print languages (standard)     HP PCL 3 GUI, JPEG       Printing paths     Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint       Drivers (included)     HP PCL 3 GUI driver for Mac OS X and Windows®       Dimensions     Printer     987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)       (w x d x h)     Shipping     1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)       Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental     Operating temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 3.4 B(A) (standby)     Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)       Power     <35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)	n²			
Memory     256 MB       Connectivity     Interfaces (standard)     Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)       Print     Printerfaces (standard)     Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce (standard)       Print languages (standard)     HP PCL 3 GUI, JPEG       Printing paths     Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint       Drivers (included)     HP PCL 3 GUI driver for Mac OS X and Windows®       Dimensions (w x d x h)     Printer     987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)       Shipping     1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)       Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental     Operating temperature: -25 to 55°C (-13 to 131°F)       Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)       Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)       Power     <35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)				
Connectivity     Interfaces (standard)     Fast Ethernet (100Base-T), Hi-Speed USB 2.0 ce Wi-Fi       Print (anguages (standard)     HP PCL 3 GUI, JPEG       Printing paths     Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint       Drivers (included)     HP PCL 3 GUI driver for Mac OS X and Windows®       Dimensions     Printer     987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)       (w x d x h)     Shipping     1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)       Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental     Operating temperature: -25 to 55°C (-13 to 131°F)       Operating humidity: 20 to 80% RH     Acoustic       Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)				
(standard)   Wi-Fi     Print languages (standard)   HP PCL 3 GUI, JPEG     Printing paths   Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint     Drivers (included)   HP PCL 3 GUI driver for Mac OS X and Windows®     Dimensions (w x d x h)   Printer   987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)     Shipping   1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)     Weight   Printer   25.5 kg (56.2 lb)     Shipping   30 kg (66.1 lb)     What's in the box   HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord     Environmental ranges   Operating temperature: 5 to 40°C (41 to 104°F)     Storage temperature: -25 to 55°C (-13 to 131°F)   Operating humidity: 20 to 80% RH     Acoustic   Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)				
(standard)   Printer driver, HP Designjet ePrint & Share, HP Instant Printing, Apple AirPrint     Drivers (included)   HP PCL 3 GUI driver for Mac OS X and Windows®     Dimensions   Printer   987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)     (w x d x h)   Shipping   1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)     Weight   Printer   25.5 kg (56.2 lb)     Shipping   30 kg (66.1 lb)     What's in the box   HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord     Environmental   Operating temperature: 5 to 40°C (41 to 104°F)     Storage temperature: -25 to 55°C (-13 to 131°F)   Operating humidity: 20 to 80% RH     Acoustic   Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)	rtified,			
HP Instant Printing, Apple AirPrint       Drivers (included)     HP PCL 3 GUI driver for Mac OS X and Windows®       Dimensions (w x d x h)     Printer     987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)       Shipping     1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)       Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental ranges     Operating temperature: 5 to 40°C (41 to 104°F)       Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)				
Dimensions (w x d x h)     Printer     987 x 530 x 285 mm (38.9 x 20.9 x 11.2 in)       Shipping     1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)       Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental ranges     Operating temperature: 5 to 40°C (41 to 104°F)       Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)				
(w x d x h)   Shipping   1141 x 620 x 415 mm (44.9 x 24.4 x 16.3 in)     Weight   Printer   25.5 kg (56.2 lb)     Shipping   30 kg (66.1 lb)     What's in the box   HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord     Environmental   Operating temperature: 5 to 40°C (41 to 104°F)     Storage temperature: -25 to 55°C (-13 to 131°F)   Operating humidity: 20 to 80% RH     Acoustic   Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)				
Weight     Printer     25.5 kg (56.2 lb)       Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental     Operating temperature: 5 to 40°C (41 to 104°F)       Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)				
Shipping     30 kg (66.1 lb)       What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental     Operating temperature: 5 to 40°C (41 to 104°F)       Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)				
What's in the box     HP Designjet T120 ePrinter, printhead, introductory ink cartridges, reference guide, setup poster, startup software, power cord       Environmental     Operating temperature: 5 to 40°C (41 to 104°F)       Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)       Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)       Power     < 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)				
box     reference guide, setup poster, startup software, power cord       Environmental ranges     Operating temperature: 5 to 40°C (41 to 104°F)       Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH       Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)       Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)       Power     < 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)				
ranges   Storage temperature: -25 to 55°C (-13 to 131°F)     Operating humidity: 20 to 80% RH     Acoustic   Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)	HP Designjet T120 ePrinter, printhead, introductory ink cartridges, quick reference guide, setup poster, startup software, power cord			
Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)       Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)       Power     < 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)	Operating temperature: 5 to 40°C (41 to 104°F)			
Acoustic     Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)       Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)	Storage temperature: -25 to 55°C (-13 to 131°F)			
Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)       Power     < 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)	Operating humidity: 20 to 80% RH			
Power     < 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)	Sound pressure: 48 dB(A) (active); < 16 dB(A) (standby)			
	Sound power: 6.5 B(A) (active); < 3.4 B(A) (standby)			
	< 35 watts (printing), < 4.5 watts (sleep), < 0.3 watts (standby)			
consumption Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/ 1200 mA max	- 3 Hz),			
Certification Safety USA and Canada (CSA certified), EU (LVD and EN compliant), Russia (GOST), Singapore (PSB), Chi Mexico (NYCE)				
Electromagnetic Compliant with Class B requirements, including (FCC rules), Canada (ICES), EU (EMC/R&TTE Direc Australia (ACMA), New Zealand (RSM), China (CC (VCCI); Certified as Class A product: Korea (KCC)	tives),			
Environmental ENERGY STAR, WEEE, EU RoHS, REACH, EuP, FE EPEAT Bronze	IP,			
Warranty One-year limited hardware warranty	_			



#### **Ordering information**

Product	CQ891A	HP Designjet T120 24-in ePrinter		
Accessories	B3Q35A	HP Designjet T120 24-in Stand		
	B3Q36A	HP Designjet T120/T520 24-in Spindle		
	J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server		
Original HP printhead	C1Q10A	HP 711 Designjet Printhead Replacement Kit		
Original HP	CZ129A	HP 711 38-ml Black Ink Cartridge		
ink cartridges	CZ130A	HP 711 29-ml Cyan Ink Cartridge		
	CZ131A	HP 711 29-ml Magenta Ink Cartridge		
	CZ132A	HP 711 29-ml Yellow Ink Cartridge		
	CZ133A	HP 711 80-ml Black Ink Cartridge		
	CZ134A	HP 711 3-pack 29-ml Cyan Ink Cartridges		
	CZ135A	HP 711 3-pack 29-ml Magenta Ink Cartridges		
	CZ136A	HP 711 3-pack 29-ml Yellow Ink Cartridges		
Original HP large format printing materials	C1860A	North America, Latin America	HP Bright White Inkjet Paper _ (FSC® certified) <sup>7</sup> 🛟 <sup>8</sup>	
	C6035A	Europe, Asia	610 mm x 45.7 m (24 in x 150 ft)	
	C6019B	HP Coated Paper (PEFC™ certified) <sup>7</sup> 🛟® 610 mm x 45.7 m (24 in x 150 ft)		
	C6029C	HP Heavyweight Coated Paper (PEFC™ certified) <sup>7</sup> 🛟 <sup>8</sup> 610 mm x 30.5 m (24 in x 100 ft)		
	CZ987A	HP Premium Satin Photo Paper (FSC® certified) <sup>7</sup> 610 mm x 15.2 m (24 in x 50 ft)		
Service and support	U1V95E	HP 3 year Next Business Day Onsite Support		
	U1W29E	HP 3 year 4-hour response, 13x5 Onsite Support <sup>9</sup>		
	U1W34PE	HP 1 year Post Warranty, Next Business Day Onsite Support <sup>9</sup>		
	U6A00PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support <sup>9</sup>		

HP Designjet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services. For more information, please visit hp.com/go/designjet/support.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks. For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

<sup>3</sup> Mechanical printing time. Printed in Fast mode on plain paper with Original HP inks.

- <sup>4</sup> Mechanical printing time with Original HP inks.
- <sup>5</sup> +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.
- <sup>6</sup> Measured on HP Matte Film.

7 FSC® trademark license code FSC®-C017543, see <u>fsc.org</u>. PEFC™ trademark license code PEFC™/29-31-198, see <u>pefc.org</u>. Not all FSC®- or <u>PEFC™</u>-certified products are available in all regions.

- <sup>8</sup> Can be recycled through commonly available recycling programs.
- <sup>9</sup> Not available in North America, and Latin America.



## For more information, please visit hp.com/go/DesignjetT120

© Copyright 2012-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

